


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61K 9/00		A2	(11) International Publication Number: WO 99/29298
			(43) International Publication Date: 17 June 1999 (17.06.99)
(21) International Application Number: PCT/US98/26156		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 9 December 1998 (09.12.98)		Published <i>Without international search report and to be republished upon receipt of that report.</i>	
(30) Priority Data: 60/069,339 11 December 1997 (11.12.97) US			
(71) Applicant: ALZA CORPORATION [US/US]; 950 Page Mill Road, P.O. Box 10950, Palo Alto, CA 94303-0802 (US).			
(72) Inventors: TRAUTMAN, Joseph, Creagan; 1574 Wright Avenue, Sunnyvale, CA 94087 (US). WONG, Patrick, S.-L.; 1533 Burlingame Avenue, Burlingame, CA 94010 (US). DADONNA, Peter, E.; 35 Anderson Way, Menlo Park, CA 94025 (US). KIM, Hyunok, Lynn; 19306 E. Braes River Drive, Walnut Creek, CA 91789 (US). ZUCK, Michael, G.; 22855 McGrath Road, Bend, OR 97701 (US).			
(74) Agents: MILLER, D., Byron et al.; Alza Corporation, 950 Page Mill Road, P.O. Box 10950, Palo Alto, CA 94303-0802 (US).			
(54) Title: DEVICE FOR ENHANCING TRANSDERMAL AGENT FLUX			
			
(57) Abstract			
<p>A device (3) comprising a sheet member (6) having a plurality of microprotrusions (4) for penetrating the skin and a rigid support (15) contacting and extending across the sheet member (6) for transmitting an applied force evenly across the length and width of the sheet member (6) to reproducibly and reliably penetrate the skin with the microprotrusions (4).</p>			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

5

DEVICE FOR ENHANCING TRANSDERMAL AGENT FLUX

TECHNICAL FIELD

10 The present invention relates to transdermal agent delivery and sampling. More particularly, this invention relates to the transdermal delivery of agents, such as peptides and proteins, through the skin, as well as the transdermal sampling of agents from the body, such as glucose, other body analytes and substances of abuse, such as alcohol
15 and illicit drugs.

BACKGROUND ART

 Interest in the percutaneous or transdermal delivery of peptides
20 and proteins to the human body continues to grow with the increasing number of medically useful peptides and proteins becoming available in large quantities and pure form. The transdermal delivery of peptides and proteins still faces significant problems. In many instances, the rate of delivery or flux of polypeptides through the skin is insufficient to
25 produce a desired therapeutic effect due to their large size/molecular weight and the resulting inability to pass through natural pathways (pores, hair follicles, etc.) through skin. In addition, polypeptides and proteins are easily degradable during penetration of the skin, prior to reaching target cells. Likewise, the passive flux of water soluble small
30 molecules such as salts is limited.

 One method of increasing the transdermal delivery of agents relies on the application of an electric current across the body surface or on "electrotransport". "Electrotransport" refers generally to the passage of a beneficial agent, e.g., a drug or drug precursor, through a body
35 surface such as skin, mucous membranes, nails, and the like. The transport of the agent is induced or enhanced by the application of an

5 electrical potential, which results in the application of electric current,
which delivers or enhances delivery of the agent. The electrotransport
of agents through a body surface may be attained in various manners.
One widely used electrotransport process, iontophoresis, involves the
electrically induced transport of charged ions. Electroosmosis, another
10 type of electrotransport process, involves the movement of a solvent
with the agent through a membrane under the influence of an electric
field. Electroporation, still another type of electrotransport, involves the
passage of an agent through pores formed by applying a high voltage
electrical pulse to a membrane. In many instances, more than one of
15 these processes may be occurring simultaneously to different extents.
Accordingly, the term "electrotransport" is given herein its broadest
possible interpretation, to include the electrically induced or enhanced
transport of at least one charged or uncharged agent, or mixtures
thereof, regardless of the specific mechanism(s) by which the agent is
20 actually being transported. Electrotransport delivery generally increases
agent delivery, particularly large molecular weight species (e.g.,
polypeptides) delivery rates, relative to passive or non-electrically
assisted transdermal delivery. However, further increases in
transdermal delivery rates and reductions in polypeptide degradation
25 during transdermal delivery are highly desirable.

One method of increasing the agent transdermal delivery rate
involves pre-treating the skin with, or co-delivering with the beneficial
agent, a skin permeation enhancer. The term "permeation enhancer" is
broadly used herein to describe a substance which, when applied to a
30 body surface through which the agent is delivered, enhances its flux
therethrough. The mechanism may involve a reduction of the electrical
resistance of the body surface to the passage of the agent therethrough,
an increase in the permselectivity and/or permeability of the body
surface, the creation of hydrophilic pathways through the body surface,
35 and/or a reduction in the degradation of the agent (e.g., degradation by
skin enzymes) during electrotransport.

5 There have been many attempts to mechanically disrupt the skin
in order to enhance transdermal flux, such as, U.S. Patent Nos.
3,814,097 issued to Ganderton et al., 5,279,544 issued to Gross et al.,
5,250,023 issued to Lee et al., 3,964,482 issued to Gerstel et al., U.S.
Patent No. Re 25,637 issued to Kravitz et al. and PCT application WO
10 96/37155. These devices typically utilize tubular or cylindrical structures
generally, although Gerstel does disclose the use of other shapes, to
pierce the outer layer of the skin. The piercing elements disclosed in
these references generally extend perpendicular from a thin flat
member, such as a pad or metal sheet. The flexible nature of the flat
15 member and the tubular shape of the piercing elements result in a
variety of short-comings, such as manufacturing difficulties, flexing of the
flat member when pressure is applied to the top of the device, uneven
penetration of the skin, poor puncturing of the skin resulting in low
transdermal flux and, for electrotransport, increased irritation due to
20 concentrating the drug flux through fewer pathways.

DESCRIPTION OF THE INVENTION

 The present invention provides a device suitable for increasing
25 transdermal flux. The device has microprotrusions which consistently
and reliably penetrate a body surface (e.g., skin) to enhance agent
delivery or sampling. The device of the present invention can be easily
manufactured in high volumes and at low cost. The device of the
present invention can penetrate the stratum comeum of skin with a
30 plurality of microprotrusions to form pathways through which a
substance such as a drug can be introduced (i.e., delivery) or a
substance such as a body analyte can be withdrawn (i.e., sampling). A
principal advantage of the present invention is that the device ensures
uniform penetration (i.e., generating the same size and depth pathways)
35 by the microprotrusions across the device. Furthermore, the present
invention reproducibly provides uniformity in penetration from patient to

5 patient.

In one aspect, the invention comprises a rigid structure which contacts and extends across a flexible device having a plurality of microprotrusions for piercing the skin. The rigid structure transmits force applied to the top of the structure substantially evenly across the flexible device and thus transmits uniform displacement of the microprotrusions. This is accomplished with substantially less dissipation of the application force in the compliant elements of the flexible device having the microprotrusions. The rigid structure provides assured transmittance of an externally applied load to the microprotrusions for easier, complete and reproducible skin penetration. The improved penetration of the skin by the microprotrusions because of the rigid structure is particularly beneficial in producing increased flux. The evenly distributed displacement of the microprotrusions provides nearly complete penetration by all of the microprotrusions so as to produce a substantial number of agent pathways and electrical continuity (if electrotransport is used) with the skin for continued and reproducible agent flux through the skin.

In one aspect of the invention, the flexible skin piercing device comprises a relatively thin flexible sheet which in use is adapted to be placed in substantially parallel relation with the body surface to be pierced. The sheet has a plurality of openings therethrough, which allow the agent to pass between a reservoir associated with the sheet (and typically positioned on the body distal surface of the sheet) and the holes pierced in the body surface by the microprotrusions. The sheet also has a plurality of microprotrusions (also referred to as micro-blades) extending approximately perpendicularly from a body proximal side of the sheet. In this aspect of the invention, a rigid support structure contacts and extends across the sheet in order to impart added structural rigidity thereto and to more evenly distribute any force applied to the device for purposes of more uniformly displacing the microprotrusions into (i.e., to pierce) the body surface. Optionally,

5 though preferably, the rigid structure forms a void for an agent reservoir.
The reservoir can be filled with an agent containing/sampling reservoir.

In a second aspect of the invention, the flexible skin piercing device comprises a relatively thin flexible sheet having a configuration defining a void or space for holding an agent-containing or agent-
10 receiving reservoir. In use, the sheet is placed in substantially perpendicular relation with the body surface to be pierced, such that the sheet has a body surface-contacting edge, said edge having a plurality of microprotrusions extending therefrom. In this aspect of the invention, a rigid support structure contacts and extends across the body distal
15 edge of the sheet in order to impart structural rigidity thereto and to more evenly distribute any force applied to the device for purposes of more uniformly displacing the microprotrusions into (i.e., to pierce) the body surface.

The device of the present invention can be used in connection
20 with agent delivery, agent sampling or both. In particular, the device of the present invention is used in connection with transdermal drug delivery, transdermal analyte sampling, or both. Delivery devices for use with the present invention include, but are not limited to, electrotransport devices, passive devices, osmotic devices and pressure driven devices.

25 Sampling devices for use with the present invention include, but are not limited to, reverse electrotransport devices, passive devices, negative pressure driven, and osmotic devices.

The device of the present invention can be used in a repeating manner in order to keep the microcuts/microslits in the body surface,
30 which microcuts/microslits are created by the microprotrusions, open for extended periods of time during transdermal delivery or sampling. This can be easily accomplished by having the patient or other medical technician periodically reapply pressure to the skin distal side of the device, causing the microprotrusions to repierce the stratum corneum
35 layer of the skin. This overcomes potential closing of the initially cut slits due to the body's natural healing processes.

5

BRIEF DESCRIPTION OF THE DRAWINGS

In the figures, like reference numerals refer to like elements in the several drawings.

10

Figure 1 is an enlarged cross-sectional view of a rigid support and skin penetrating member taken along line 1-1 in Figure 2;

Figure 2 is a top plan view of the rigid support of Figure 1;

15

Figure 3 is an enlarged perspective view of the bottom side of a skin penetrating device with a connecting medium removed therefrom for clarity in accordance with one embodiment of the present invention;

20

Figures 4, 6 and 7 are top plan views of other embodiments of the rigid support;

Figure 5 is an exploded perspective view of an alternate embodiment of the rigid support and skin penetrating member;

25

Figure 8 is a side view of another embodiment of a support and skin penetrating member in accordance with the present invention;

Figure 9 is a top view of still another embodiment of the support member of the present invention;

30

Figure 10 is a perspective exploded view of yet another embodiment of the support of the present invention;

35

Figure 11 is a sectional perspective exploded view of still another embodiment of the support of the present invention;

5

Figure 12 is a perspective view of a hand-held device having a support in accordance with another embodiment of the present invention;

10

Figure 13 is an exploded perspective view of one embodiment of an electrotransport agent delivery/sampling system according to one embodiment of the present invention;

15

Figure 14 is a bottom plan view of the electrotransport agent delivery/sampling system of Figure 13;

Figure 15 is a right side elevational view of the electrotransport agent delivery/sampling system of Figure 13;

20

Figure 16 is a rear elevational view of the electrotransport agent delivery/sampling system of Figure 13;

25

Figure 17 is a cross-sectional view taken along line 17-17 of the assembled electrotransport agent delivery/sampling system of Figure 15; and

Figure 18 is a diagrammatic cross-sectional view of a passive agent delivery/sampling system in accordance with one embodiment of the present invention.

30

MODES FOR CARRYING OUT THE INVENTION

Turning now to the drawings in detail, the device 2 of the present invention is generally shown in Figure 1 comprising skin penetrating sheet member 6 and support member 15. Device 2 is used to enhance the transdermal delivery or sampling of an agent. The terms "substance", "agent" and "drug" are used interchangeably herein and

35

5 broadly include physiologically or pharmacologically active substances for producing a localized or systemic effect or effects in mammals including humans and primates, avians, valuable domestic household, sport or farm animals, or for administering to laboratory animals such as mice, rats, guinea pigs, and the like. These terms also include
10 substances such as glucose, other body analytes that are found in the tissue, interstitial fluid and/or blood, alcohol, licit substances, and illicit drugs, etc. that can be sampled through the skin.

The major barrier to the transdermal flux of agents (e.g., drugs to be delivered and analytes to be sampled) is the outermost layer (i.e.,
15 stratum corneum). The inner division of the epidermis generally comprises three layers commonly identified as stratum granulosum, stratum malpighii, and stratum germinativum. There is essentially little or no resistance to transport or to absorption of an agent through the stratum granulosum, stratum malpighii, and stratum germinativum.
20 Device 2 comprises a rigid support member 15 and a compliant sheet member 6 (see Figure 3 in which device 2 is in an inverted position to show the microprotrusions) having a plurality of microprotrusions 4 extending outwardly therefrom. The device 2 is pressed against an area of skin through which an agent is to be transdermally delivered or
25 sampled. The microprotrusions 4 form tiny slits in the skin and penetrate at least through the stratum corneum so that the agent is conducted through the skin with little or no resistance. Typically, the microprotrusions penetrate the skin to a depth of up to 500 μm , more typically to a depth of 50 to 300 μm . The microprotrusions 4 can be
30 microblades (Figures 1 and 3), pins (not shown), or any of a variety of configurations for piercing the skin or body surface. The microprotrusions 4 penetrate the stratum corneum of the epidermis when pressure is applied to the top of the support member 15 to increase the administration of, or sampling of, an agent through a body
35 surface. The term "body surface" as used herein refers generally to the skin, mucous membranes, and nails of an animal or human, and to the

5 outer surface of a plant. The microprotrusions 4 penetrate the body surface to create good agent conduction from the system into the body, or vice versa.

In the embodiments shown in Figures 1-3, the sheet member 6 is formed with a plurality of openings 8, each opening 8 having at least one
10 microprotrusion 4 along the periphery thereof. The microprotrusions 4 cut microslits in the stratum corneum, thereby enhancing the transdermal flux of agent released from or collected in the agent containing or collecting reservoirs 27 housed by the plurality of voids 7.

Sheet member 6 can be composed of metal, silicon or plastic,
15 although metals such as stainless steel and titanium are preferred. Sheet member 6 is generally compliant and flexible because of its relatively thin thickness. For example, when sheet member 6 is comprised of a metal such as stainless steel or titanium, the sheet member 6 will typically have a thickness of only about 5 μm to about 100
20 μm , and more typically about 25 μm to about 50 μm .

In accordance with the present invention, a rigid structural support member 15 having greater rigidity than the sheet member 6 is placed across the sheet member 6 (Figures 1 and 2). The support member 15 prevents deformation or flexing of sheet member 6 as the device 2 is
25 applied to the body surface and a downward force (i.e., directed toward the body surface being pierced) is applied in order to cause the microprotrusions 4 to pierce the body surface. The support member 15 should be sufficiently rigid to deflect less than 300 μm , and more preferably less than 50 μm , under manually applied finger or hand
30 pressing of the device 2 against the skin. Support member 15 can be a variety of configurations, for example but not limited to the embodiments shown in Figures 1, 2, 4-8 and 13. In the embodiment shown in Figures 1 and 2, support member 15 is a rigid structure which forms a plurality of voids 7, extending through the thickness of the support member, which
35 voids 7 collectively house reservoir 27 (Figure 1) for containing the agent that is to be delivered or for receiving the agent that is to be sampled.

5 Between the voids 7 are a plurality of supports or cross-members 5 which are in contact with and extend across the width or length of the sheet member 6. The cross-members 5 transmit force that is applied to the top of the device 3 evenly across the sheet member 6 so that each of the microprotrusions 4 are displaced (into the skin) the same amount
10 for more even penetration of the skin by the microprotrusions 4. When used with a transdermal electrotransport device, the sheet member 6 and/or support member 15 are preferably electrically isolated or insulated from the current conducting elements (e.g., the electrodes) of the electrotransport device in order to avoid short circuiting the drug
15 reservoir. This can be achieved by using electrically non-conducting, electrically insulative materials or coatings for sheet member 6 and/or support member 15.

Preferably the support member 15 also has a low compressibility. Optimally, the support member 15 compresses a distance of less than
20 250 μm , and more preferably less than 50 μm , during manually applied finger or hand pressing of the device against the skin. Most preferably, the support member 15 will exhibit a combined flexibility and compressibility of less than about 250 μm during manually applied finger or hand pressing of the device against the skin.

25 The support member 15 maybe made from any material having the aforementioned high rigidity, and preferably the aforementioned low compressibility. Suitable materials include metals, metal alloys, ceramics, glasses, rigid plastics, and reinforced (e.g., carbon fiber reinforced).

30 Various embodiments of the support member are illustrated in Figures 2 and 4-13. In the embodiments shown in Figures 2, 4-7 and 13, the support member 15 is comprised of a peripheral (e.g., annular) wall 53 having at least one cross-member 5 extending across the support member 15 so as to create a plurality of voids 7 which house the
35 reservoir for the agent and to distribute an applied force substantially evenly across the sheet member 6 (i.e, without bending or flexing the

5 sheet 6). The cross-members generally extend diagonally in Figures 4, 5, 6 and 13 across the volume bounded by the outer wall of the support member 15. Diagonal, as used herein, is meant to describe embodiments other than cross-members joining two vertices of a rectilinear figure that are nonadjacent or passing through two
10 nonadjacent edges of a polyhedron, as is apparent from the embodiments shown in the figures. As can be seen, the cross-members include oblique (Figure 6) and non-oblique (Figure 7) cross-members as well as honeycomb configurations (Figure 2). The number of cross-members depends on a variety of factors, for example, the relative
15 structural integrity or flexibility of the sheet member 6 and the support member 15, the distance across the support member 15, the size of the agent reservoir skin-contact area, and the volume of the agent reservoir. In general, when using sheet member 6 formed of very thin metal, the maximum distance between adjacent cross-members 5 in support
20 member 15 will be no more than about 4 times, and preferably no more than about 2 times, the distance between adjacent microprotrusions 4 in sheet member 6. Figure 7 illustrates that the support member 15 can be comprised of a plurality of inner annular walls 55 connected by the cross-members 5 to the outer annular wall 53.

25 Figure 5 illustrates an alternate embodiment of the sheet member 6 wherein the microprotrusions 4 extend outwardly from a body contacting edge 49 of a thin, sheet member 6. In this embodiment, the plane of the sheet member 6 is oriented in a roughly perpendicular relation to the body surface during use. The sheet member 6 has a
30 spiral configuration which defines voids 51 for holding an agent-containing or an agent-receiving reservoir (not shown in Figure 5). Coiling, folding (not shown), and curving (not shown) as well as other forms of forming the sheet member 6 from its generally planar state along its length to form a structure having a plurality of voids 51 can also
35 be used. In a preferred embodiment, voids 51 are in communication with the voids 7 of the support member 15.

5 The surface of support member 15 which contacts the skin distal side/edge of sheet member 6 is generally shown as flat (i.e., planar) in Figures 1 and 5. Most preferably however, the surface of support member 15 which contacts the sheet member 6 has a convex or curved (e.g., cylindrically shaped) surface 54 as best shown in Figure 8. The
10 radius of curvature of the convex or cylindrically shaped surface 54 is preferably more than about 5 cm, more preferably more than about 10 cm.

 Figure 9 illustrates an alternate embodiment of the support member 15. In this embodiment, support member 15 is comprised of a
15 plurality of strips which have a wavy shape and are oriented perpendicularly with respect to the plane of sheet member 6. Sheet member 6 has the same configuration shown in Figure 3 with openings 8 therein and associated microprotrusions 4 (not shown in Figure 9). The wavy strips 91, 93 are preferably fixed together at their contact points 95
20 such as by welding in the case where the sheets 91, 93 are composed of metal or plastic. The wavy configuration of the adjacent strips 91, 93 create voids 97 therebetween for containing an appropriate reservoir material. Thus, the height of strips 91 and 93 will be governed in part by the thickness of the reservoir material loaded into voids 97.

25 Figure 10, illustrates yet another embodiment of the support member 15. In this embodiment, support member 15 is comprised of a corrugated sheet 101. Corrugated sheet 101 is adapted to contact the skin distal side of sheet member 6. If necessary, a cover sheet (not shown in Figure 10) covering the skin distal side of corrugated sheet
30 101, or rails (not shown in Figure 10) along the side edges of corrugated sheet 101, can be used to provide additional rigidity and to prevent any tendency for the sheet 101 to bend or fold along the corrugation folds when force is applied to the skin distal side of sheet 101. Optionally, corrugated sheet 101 may have a plurality of openings therein, thereby
35 making it possible for agent to move through the corrugated sheet 101. The size and number of openings (not shown in Figure 10) is not critical

5 as long as the structural integrity and rigidity of the corrugated sheet 101 is not compromised. This would make it possible to place additional reservoir material into the voids 104 adjacent to the skin distal side of sheet 101. As in the other embodiments, a reservoir material can be loaded into the voids 103 formed between the corrugations and the
10 underlying sheet member 6 (not shown in Figure 10).

Figure 11 discloses an alternate embodiment of a corrugated sheet 101 in which the corrugation folds are not all parallel to one another. Similar to the device of Figure 10, the Figure 11 device can also be provided, if necessary, with a covering sheet over the skin distal
15 side of corrugated sheet 101, or alternatively with an annular rail surrounding corrugated sheet 101, in order to enhance the structural rigidity of corrugated sheet 101. Still further as in the Figure 10 device, the Figure 11 device can be provided with a plurality of openings (not shown in Figure 11) in the corrugated sheet 101 in order to allow agent
20 delivery therethrough. Such openings make it possible to utilize voids 104 to contain agent reservoir material.

A common feature of the support members 15 illustrated in Figure 1-2, 4-7, 9-11 and 13 is that the support member 15 contains voids (e.g., voids 7, 97 and 103) into which a reservoir material can be loaded. On
25 the other hand, certain embodiments of the sheet member 6 such as that shown in Figure 5 have their own voids 51 for containing the reservoir material. In cases such as this and also in cases where the sheet member 6 is applied to the skin as a pretreatment step prior to placing an agent-containing/sampling reservoir on the pretreated skin
30 site, the support member 15 need not be integrally a part of or otherwise fixedly attached to the sheet member 6.

Figure 12 illustrates a support member 115 which is the head of a hand-held device 112 used to press sheet member 6 into the skin. The head 115 is typically comprised of a metal plate having sufficient
35 thickness (e.g., 0.5 cm or more) to impart sufficient rigidity thereto. The support member 115 is attached to device 112 by means of screw-

5 threads 113. The surface 111 is pressed against the sheet member 6 in order to force the microprotrusions 4 to puncture the skin. Surface 111 may have either a convex curvature (as shown in Figure 12 and as discussed earlier in connection with Figure 8) or can be simply a flat (i.e., planar) surface. Optionally, device 112 can be spring-loaded in
10 order to cause support member 115 to impact the skin distal side of sheet member 6 with a predetermined force.

Although the support member 15 of the present invention has been described primarily in connection with the initial application and piercing of body tissue (e.g., skin) by sheet member 6 and
15 microprotrusion 4, those skilled in the art will appreciate that the rigid support member 15 is also useful for reapplication (i.e., subsequent application) of the sheet member 6 and subsequent piercing by the microprotrusions 4, either at the same body surface site as the first application or at a new body surface site. The subsequent piercing of
20 the skin by the microprotrusions 4 at the original body surface site (i.e., the body surface site through which the microprotrusions 4 initially pierced) is useful in keeping the microcuts/microslits cut by the microprotrusions 4 open so that transdermal agent flux can continue unimpeded. Transdermal drug delivery/sampling devices, such as that
25 disclosed in Figures 13-18, typically are adapted to adhere to the skin during transdermal delivery or sampling. After the microprotrusions 4 initially create microcuts/microslits through the stratum corneum, the skin immediately begins a healing process. Eventually, the microslits will close off as the healing process continues. Thus, reapplication of finger
30 pressure to reapply the sheet member 6 against the skin is desirable in order to keep the microslits open and the transdermal agent flux unimpeded. This can be easily accomplished with the support structure of the present invention. When the transdermal delivery/sampling device is adhered to the skin, the patient or technician can simply
35 periodically reapply finger or hand pressure to the skin distal side of the device in order to cause the microprotrusions 4 to repierce the stratum

5 corneum.

 The microprotrusions or microblades 4 are generally formed from a single piece of material and are sufficiently sharp and long for penetrating at least the stratum corneum of the skin. In one embodiment, the microprotrusions 4 and the sheet member 6 are
10 essentially impermeable or are impermeable to the passage of an agent. The width of each microprotrusion can be any of a range of widths. The width of the microprotrusion at the intersection of the microprotrusion and the body surface after the microprotrusion array has been inserted is typically at least about 25 mm. The required length of the blades is
15 subject to variation of the body surface being penetrated and corresponds to at least the natural thickness of the stratum corneum, for one of the principal features of the invention is that the microprotrusions are to penetrate at least through the stratum corneum and into the epidermis. Usually, the microprotrusions will have a length and
20 configuration which achieves a depth of penetration of about 25 mm to about 400, with the depth of penetration for most applications being between about 50 mm to about 200 mm. The microprotrusions 4 can have slanted (i.e., angled) leading edges 64 (Figure 3) to further reduce the insertion force required to press the microprotrusions into the skin
25 tissue. The leading edges of each microprotrusion 4 can all be the same angle or can be at different angles suitable for penetrating the skin. Alternatively, the leading edge of each microprotrusion can be curved having, for example, a convex or concave shape or be divided into any number of angled segments such as the first segment being relatively
30 steep with respect to vertical and the second segment being more gradually angled with respect to vertical.

 The sheet member 6 can be produced with a photolithography process followed by a chemical etching process followed by a micropunching operation as disclosed in WO 97/48440, the disclosures
35 of which are incorporated herein by reference. The embodiment of sheet member 6 illustrated in Figure 5 requires an additional step of

5 forming the planar sheet member 6 into the desired void-defining shape (i.e., spiral, serpentine, concentric circles, etc.). This can be accomplished using well-known metal sheet bending, rolling, folding and/or shaping techniques.

Generally, the microprotrusions 4 are at an angle of about 90° to the surface 48 (Figure 3) of the sheet member 6 after being punched, but they can be disposed at any angle forward or backward from the perpendicular position that will facilitate penetration of the stratum corneum.

The sheet member 6 and microprotrusions 4 can be made from materials that have sufficient strength and manufacturability to produce microprotrusions, such as, glasses, ceramics, rigid polymers, reinforced (e.g., carbon fiber reinforced) polymers, metals and metal alloys. Examples of metals and metal alloys include but are not limited to stainless steel, iron, steel, tin, zinc, copper, gold, platinum, aluminum, germanium, zirconium, titanium and titanium alloys. Each of the sheet member and microprotrusions can have a thin layer of gold, platinum, iridium, titanium, or rhodium plating. Examples of glasses include silicas and devitrified glasses such as "PHOTOCERAM" available from Corning in Corning, NY. Examples of polymers include but are not limited to polystyrene, polymethylmethacrylate, polypropylene, polyethylene, "BAKELITE", cellulose acetate, ethylcellulose, styrene/acrylonitrile copolymers, styrene/butadiene copolymers, acrylonitrile/butadiene/styrene (ABS) copolymers, polyvinyl chloride and acrylic acid polymers including polyacrylates and polymethacrylates.

30 The number of microprotrusions 4 and openings 8 of any of the embodiments of the sheet member 6 is variable with respect to the desired flux rate, agent being sampled or delivered, delivery or sampling device used (i.e., electrotransport, passive, osmotic, pressure driven, etc.), and other factors as will be evident to one of ordinary skill in the art. In general, the larger the number of microprotrusions per unit area 35 (i.e., microblade density), the less concentrated the flux (per microslit) of

5 the agent in the skin because there are a greater number of pathways through the skin. Consequently, a smaller number of microprotrusions per unit area leads to the transport of the agent through the skin becoming more concentrated in fewer pathways. Higher concentrations of agents in a skin pathway can lead to higher incidences and/or severity
10 of skin reactions (e.g., irritation). Therefore, larger microblade densities reduce the incidence and/or severity of skin reactions.

An optional connecting medium (not shown) can be predisposed on the skin contacting side 48 of the sheet member 6 having the configuration shown in Figures 1-3 as taught in WO 98/28037, the
15 disclosures of which are incorporate herein by reference. The connecting medium, if used, acts as a conduit for the agent and acts as a bridge between the agent containing or collecting reservoir and the skin, thus allowing an agent to be transported unhindered therethrough.

One type of transdermal delivery/sampling device, which can be
20 used with the present invention relies on the application of an electric current across the body surface or "electrotransport". It will be appreciated by those working in the field that the present invention can be used in conjunction with a wide variety of electrotransport systems, as the invention is not limited in any way in this regard. For examples of
25 electrotransport systems, reference may be had to U.S. Patent Nos. 5,147,296 to Theeuwes et al., 5,080,646 to Theeuwes et al., 5,169,382 to Theeuwes et al., 5,423,739 to Phipps et al., 5,385,543 to Haak et al., 5,310,404 to Gyory et al., and 5,169,383 to Gyory et al., of which any of the disclosed electrotransport systems can be used with the present
30 invention.

Figures 13-17 illustrate a representative electrotransport delivery/sampling device 10 that may be used in conjunction with a support member 15 and a skin penetrating device 2 in accordance with the present invention. Device 10 comprises an upper housing 16, a
35 circuit board assembly 18, a lower housing 20, donor electrode 22, counter electrode 24, donor reservoir 27, counter reservoir 28 and skin-

5 compatible adhesive 30. Upper housing 16 has lateral wings 31 which assist in holding device 10 on a patient's skin. Printed circuit board assembly 18 comprises an integrated circuit 19 coupled to discrete components 40 and battery 32. Circuit board assembly 18 is attached to housing 16 by posts 33 (only one shown in Figure 17) passing through
10 openings 13a and 13b, the ends of the posts being heated/melted in order to heat stake the circuit board assembly 18 to the housing 16. Lower housing 20 is attached to the upper housing 16 by means of adhesive layer 30, the upper surface 34 of adhesive layer 30 being adhered to both lower housing 20 and upper housing 16 including the
15 bottom surfaces of wings 31. Shown (partially) on the underside of circuit board assembly 18 is a button cell battery

32. Other types of batteries may also be employed to power device 10 depending on the need.

20 The device 10 is generally comprised of battery 32, electronic circuitry 19,40, electrodes 22,24, counter reservoir 28, support member 15 housing donor reservoir 27, and skin penetrating device 2, all of which are integrated into a self-contained unit. Electrodes 22,24 and reservoirs 27,28 are retained by lower housing 20. The outputs (not
25 shown in Figure 13) of the circuit board assembly 18 make electrical contact with the electrodes 24 and 22 through openings 23,23' in the depressions 25,25' formed in lower housing 20, by means of electrically conductive adhesive strips 42,42'. Electrodes 22 and 24, in turn, are in direct mechanical and electrical contact with the top sides 44',44 of
30 reservoirs 27 and 28. The bottom side 46 of counter reservoir 28 contacts the patient's skin through the opening 29 in adhesive layer 30. The bottom side 46' of donor reservoir 27 contacts the patient's skin through the plurality of openings 8 in the skin penetrating device 2 as best shown in Figure 1. The agent in donor reservoir 27 is typically in
35 the form of a solution, most preferably an aqueous solution, which solution is contained in a solid matrix material such as a sponge, a

5 hydrophilic polymer matrix (e.g., a hydrogel) which allows free mobility of the agent therethrough. The reservoir matrix material fills the openings 8 such that the agent reservoir is in contact with the body surface as can be seen in Figure 1. As discussed above, a connecting medium can be placed as a layer on the skin-proximal side of sheet 6, with the
10 microblades 4 passing therethrough. The optional connecting medium provides a more consistent agent flow pathway between the donor reservoir 27 and the skin. Typically the agent is present initially in both the reservoir and the connecting medium because of diffusion or because the reservoir and connecting medium are the same material.

15 The device 10 adheres to the patient's body surface (e.g., skin) by means of a peripheral adhesive layer 30 (which has upper adhesive side 34 and body-contacting adhesive side 36) and, optionally, anchoring elements on the device 2 of any of the embodiments discussed herein. Further, optionally, the connecting medium 65 can be tacky or adhesive
20 for assisting in maintaining interface contact with the skin. The adhesive side 36 covers the entire underneath side of the device 10 except where the device 2 and counter electrode reservoir 28 are located. The adhesive side 36 has adhesive properties which assures that the device 10 remains in place on the body during normal user activity, and yet
25 permits reasonable removal after the predetermined (e.g., 24-hour) wear period. Upper adhesive side 34 adheres to lower housing 20 and retains the electrodes and agent reservoirs within housing depression 25, 25' as well as retains device 2 to lower housing 20 and lower housing 20 to upper housing 16.

30 In one embodiment of the agent delivery/sampling device there is a release liner (not shown) on the device 10 for maintaining the integrity of adhesive layer 30 when the device is not in use. In use, the release liner is stripped from the device before the device is applied to the skin. Device 10 also has a push button switch 12, which when pressed turns
35 the device 10 on which is made apparent to the user by means of LED 14 becoming lit. Agent is delivered through the patient's skin (e.g., on

5 the arm) by electrotransport over a predetermined delivery interval.

In other embodiments of the present invention, passive transdermal delivery or sampling devices are used with the support member 15 predisposed on the top surface of the member 6. It will be appreciated by those working in the field that the present invention can be used in conjunction with a wide variety of passive transdermal systems, as the invention is not limited in this regard. For examples of passive systems, reference may be had to, but not limited to, U.S. Patent Nos. 4,379,454 to Campbell, et al., 4,588,580 to Gale et al., 4,832,953 to Campbell et al., 4,698,062 to Gale et al., 4,867,982 to Campbell et al., and 5,268,209 to Hunt et al., of which any of the disclosed systems can be used with the present invention. One example of a passive transdermal delivery/sampling device is illustrated in Figure 18. Support member 15 having the edges of sheet member 6 embedded in the outer annular wall 53 thereof is housed in a foam pad or band 57 which can be applied to the body surface. The edges of sheet member 6 need not be embedded in the outer annular wall, as the sheet member 6 can be attached to the support member 15 as described in the previous embodiments. Extending across annular wall 53 and cross-member 5 is a rigid top 59. Top 59 is sufficiently rigid so as not to deform when force is applied thereto and so as to more evenly transmit the applied force and displacement of microprotrusions 4 across the length and width of sheet member 6. Preferably, although not required, the passive delivery/sampling device has a peripheral adhesive on the body-contacting surface of foam pad 57 and an adhesive interface gel (not shown) on the body-contacting side of the member 2.

It will be appreciated by those working in the field that the present invention can also be used in conjunction with a wide variety of osmotic and pressure driven systems, as the invention is not limited to a particular device in this regard. For examples of osmotic and pressure driven devices, reference may be had to U.S. Patent Nos. 4,340,480 to Eckenhoff, 4,655,766 to Theeuwes et al., 4,753,651 to Eckenhoff,

5 5,279,544 to Gross et al., 4,655,766 to Theeuwes, 5,242,406 to Gross et al., and 4,753,651 to Eckenhoff any of which can be used with the present invention.

This invention has utility in connection with the delivery of agents within any of the broad class of drugs normally delivered through body
10 surfaces and membranes, including skin. In general, this includes drugs in all of the major therapeutic areas. The invention is also useful in the transdermal delivery of proteins, peptides and fragments thereof, whether naturally occurring, chemically synthesized or recombinantly produced. The invention may additionally be used in conjunction with
15 the delivery of vaccines, nucleotidic drugs, including oligonucleotide drugs, polynucleotide drugs, and genes. These substances typically have a molecular weight of at least about 300 daltons, and more typically have a molecular weight of at least about 300 to 40,000 daltons.

As mentioned, the device 2 of the present invention can also be used
20 with sampling devices including, but not limited to, reverse electrotransport (i.e., reverse iontophoresis and/or reverse electroosmosis in the case of sampling uncharged materials such as glucose), osmosis, and passive diffusion. For example, reference may be had to U.S. Patent Nos. 4,756,314 to Eckenhoff et al., 5,438,984 to
25 Schoendorfer, 5,279,543 to Glikfeld et al., and 5,362,307 to Guy et al.

It will be appreciated by those of ordinary skill in the art that the invention can be embodied in other specific forms without departing from the spirit or essential character thereof. The presently disclosed
embodiments are therefore considered in all respects to be illustrative
30 and not restrictive. The scope of the invention is indicated by the appended claims rather than the foregoing description, and all changes which come within the meaning and range of equivalents thereof are intended to be embraced therein.

5 CLAIMS:

1. A device (2) for use in introducing or withdrawing an agent through a body surface, comprising a member (16) having a plurality of microprotrusions (4) extending from a body surface proximal portion (48)
10 of the member (16), the device being characterized by
a structural support (15) which contacts and extends across at least a portion of the member (6), the support (15) having greater rigidity than the member (6).
- 15 2. The device of claim 1, wherein the support (15) has greater rigidity to a force applied perpendicular to the body surface than does the member (6).
3. The device of claim 1, wherein the support (15) is sufficiently rigid
20 to deflect less than 300 μm under manually applied finger or hand pressing of the device (2) against skin.
4. The device of claim 3, wherein the support (15) deflects less than 50 μm under said pressing.
- 25 5. The device of claim 1, wherein the support (15) is sufficiently incompressible to compress less than 250 μm under manually applied finger or hand pressing the device (2) against skin.
- 30 6. The device of claim 5, wherein the support (15) compresses less than 50 μm under said pressing.
7. The device of claim 1, wherein the member (6) comprises a sheet which in use is oriented approximately parallel to the body surface, the
35 sheet having a plurality of openings (8) therein and the plurality of microprotrusions (4) extending from a body proximal surface (48) of the

5 sheet, said microprotrusions (4) being adapted to pierce the body surface.

8. The device of claim 1, wherein the structural support (15) defines a void (7) for an agent-containing or agent-receiving reservoir.

10 9. The device of claim 7, wherein the reservoir is in agent-transmitting communication with the openings (8) in the sheet.

10. The device of claim 1, wherein the support (15) comprises a peripheral member (53) and a plurality of cross-members (5).

15

11. The device of claim 1, wherein the support (15) has a honeycomb structure.

12. The device of claim 1, wherein the support (15) comprises a
20 corrugated sheet (101).

13. The device of claim 1, wherein the support has a curved surface (54) which contacts the member (6).

25 14. The device of claim 13, wherein the curved surface (54) has a shape selected from the group consisting of convex and cylindrical.

15. The device of claim 7, wherein the support (15) comprises a plurality of wavy strips (91, 93) arranged in perpendicular alignment to
30 the sheet (6).

16. The device of claim 1, wherein the sheet (6) has a thickness of less than 100 μm .

35 17. The device of claim 16, wherein the sheet (6) is comprised of metal.

5

18. The device of claim 1, wherein the member (6) comprises a sheet having the plurality of microprotrusions extending from a body surface proximal edge (49) of the sheet (6) for piercing the body surface, the sheet (6) when in use being oriented in an approximately perpendicular
10 relation to the body surface with the body surface proximal edge (49) having the microprotrusions (4) engaging the body surface.

19. The device of claim 18, wherein the sheet has a configuration which defines a void (51) for an agent-containing or agent-receiving
15 reservoir.

20. The device of claim 18, wherein the support (15) contacts a second edge of the sheet, which second edge is opposite to the body surface proximal edge (49) having the microprotrusions (4).

20

21. A method of maintaining open agent-transmitting pathways through a body surface having the device (2) of claim 1 positioned adjacent thereto, comprising periodically reapplying a body surface directed force to said device (2).

25

22. The device of claim 21, wherein said reapplying causes said microprotrusions (4) to repierce the body surface.

23. The method of claim 21, wherein said force is applied manually.

30

24. The method of claim 21, wherein the structural support (15) comprises an annular member (53).

25. The method of claim 24, wherein the annular member (53) is a
35 circular, square or rectangular annular member having a diagonal cross-member (5).

5

26. The method of claim 21, wherein the structural support (15) has a plurality of cross-members (5).

27. The method of claim 26, wherein the plurality of cross-members
10 (5) intersect generally in the center of the structural support (15).

28. The method of claim 21, wherein the structural support comprises:

an outer annular member (53);

an inner annular member (55) having a diameter less than a
15 diameter of the outer annular member (53); and
the cross-member (5) joins the inner annular member (55) to the outer annular member (53).

29. The method of claim 21, wherein the support (15) has greater
20 rigidity to a force applied perpendicular to the body surface than does the member (6).

30. The method of claim 21, wherein the support (15) is sufficiently rigid to deflect less than 300 μm under manually applied finger or hand
25 pressing of the device (2) against skin.

31. The method of claim 30, wherein the support (15) deflects less than 50 μm under said pressing.

32. The method of claim 21, wherein the support (15) is sufficiently
30 incompressible to compress less than 250 μm under manually applied finger or hand pressing of the device against skin.

33. The method of claim 32, wherein the support compresses less
35 than 50 μm under said pressing.

5 34. The method of claim 21, wherein the member (6) comprises a
sheet which in use is oriented approximately parallel to the body surface,
the sheet having a plurality of openings (8) therein and the plurality of
microprotrusions (4) extending from a body proximal surface (48) of the
sheet, said microprotrusions (4) being adapted to pierce the body
10 surface.

35. The method of claim 21, wherein the structural support (15)
defines a void.




15




20

25

30

35
\\





3/9

FIG. 7





FIG. 8




FIG. 9

5/9




FIG. 10




FIG. 11

6/9





FIG. 12

FIG. 13



8/9




FIG. 14




FIG. 15

9/9




FIG. 16




FIG. 17




FIG. 18

